



Notes:

1. Electrical Specifications:
 - Meets USB 2.0 Specification
 - Contact Resistance: 30 mOhm max.
 - Insulation Resistance: 1000 MOhm min. @ 100 VDC
 - Current Rating: 1.5 A max. at 25° C
 - Working Voltage: 30 V (RMS) max.
 - DWV: 500 VAC/60s at sea Level
 - Operating Temperature: -40° C to +85° C
2. Material and Finish:
 - Coupling Ring and Plug Housing: Polyester (Black), UL94 V-0 or Metallized ABS (Nickel Plated), UL94 V-0
 - Interfacial Seal: Silicon, Color: White
 - Cable Fitting: PA (Black), UL94 V-0
 - Cable Fitting Rubber Ring: NBR, Color: Black
 - USB Metal Shell: SPCC, Nickel Plated
 - USB Insulator: PBT, UL94 V-0, White
 - USB Contacts: Copper Alloy,
 - USB Contact Finish: 30 u" Gold min. over Nickel for mating area, Tin over Nickel for solder cup
3. USB Type A Plug accepts AWG28 to AWG24 wires, Cable OD of 4.0 mm to 5.5 mm
4. IP67 rated when fully mated with the appropriate mating connector

RoHS Compliant

Version	Part Number
Plastic Version	17-200121
Metallized Plastic Version	17-200131

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY MANNER AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC CORPORATION. DO NOT ALTER CAD DRAWING BY HAND	Customer:			Tolerance Unless otherwise specified			Scale: 1.5:1	Dim. in mm
	Name	Title	Approval Date	0 PLC ±0.50	1 PLC ±0.38		Autodesk Inventor Title: IP67 USB USB 2.0 Type A Plug Assembly Kit Solder Cup Version	Material: See Notes
	f	1 x f	Apr/21/2017	Vincent Ke	2 PLC ±0.25	2008		Date
	e	2 x e	Jun/23/2014	Vincent Ke	3 PLC ±0.10	Draw.	Sept. 09	Vincent Ke
	d	1 x d	Jan/06/2012	Vincent ke	ANGLES ±3°	Appd.	Sept. 09	J. Chaudry
c	1 x c	Mar/18/2010	Vincent ke		Norm			
b	1 x b	Jun/01/2009	Vincent ke		D-old			
a	original							
Rev.	Changes	Date	Name			Drawing No.: 39K1A364		DIN A3
						Part No.: SEE PART NUMBER TABLE		Sheet 1/1