## SIEMENS

## Data sheet

## 6ES7193-6BP20-0BB0



SIMATIC ET 200SP, BaseUnit BU20-P12+A4+0B, BU type B0, Push-in terminals, with 4 AUX terminals, bridged to the left, WxH: 20 mmx117 mm

General information	
Product type designation	ET 200SP, BaseUnit BU-Typ B0, PU 1
HW functional status	FS10 and higher
Supply voltage	
Rated value (DC)	
<ul> <li>For P1 and P2 bus</li> </ul>	24 V
<ul> <li>For AUX bus</li> </ul>	24 V; Equal potential group to P1/P2 bus or PE
for process terminals	24 V
Rated value (AC)	
<ul> <li>For P1 and P2 bus</li> </ul>	230 V
<ul> <li>For AUX bus</li> </ul>	230 V; Equal potential group to P1/P2 bus or PE
<ul> <li>for process terminals</li> </ul>	230 V
Mains filter	
integrated	No
Current carrying capacity	
up to 60 °C, max.	10 A
For P1 and P2 bus, max.	10 A
For AUX bus, max.	10 A
For process terminals, max.	5 A
Hardware configuration	
Automatic encoding	Yes
Slots	
<ul> <li>Number of slots</li> </ul>	1
Potential separation	
between backplane bus and supply voltage	Yes
between process terminals and supply voltage	Yes
between power bus and supply voltage	No
Isolation	
Isolation tested with	3 100 V DC
Ambient conditions	
Ambient temperature during operation	
<ul> <li>horizontal installation, min.</li> </ul>	-30 °C
<ul> <li>horizontal installation, max.</li> </ul>	60 °C
<ul> <li>vertical installation, min.</li> </ul>	-30 °C
<ul> <li>vertical installation, max.</li> </ul>	50 °C
Altitude during operation relating to sea level	
<ul> <li>Installation altitude above sea level, max.</li> </ul>	2 000 m; On request: Installation altitudes greater than 2 000 m

Accessories	
Color coding labels	
<ul> <li>for AUX terminals</li> </ul>	CC81 to CC83
Connection method	
Terminals	
Terminal type	Push-in terminal
Conductor cross-section, min.	0.14 mm²
<ul> <li>Conductor cross-section, max.</li> </ul>	2.5 mm <sup>2</sup>
<ul> <li>Number of process terminals to I/O module</li> </ul>	12; Pro slot
<ul> <li>Number of terminals to AUX bus</li> </ul>	0
<ul> <li>Number of add-on terminals</li> </ul>	0
<ul> <li>Number of terminals with connection to P1 and P2 bus</li> </ul>	0; Pro slot
Dimensions	
Width	20 mm
Height	117 mm
Depth	35 mm
Weights	
Weight, approx.	48 g

last modified:

12/19/2020 🕑